

10K CAST STAINLESS STEEL,BALL VALVES

KITZ Fig:10UTBM

Sizes: 1/2-8inch(15-200mm)

Anti-static Device,Full Bore,Flanged Ends.

Standards

- End to End: KITZ STANDARD
- End Connection: JIS B2220 10K
- Wall Thickness: ASME B16.34 CLASS 150

Test Standard

- KITZ STANDARD

Dimensions

SIZE(inch/mm)		L	H	D1	Kg	
1/2	15	110.0	102.0	130.0	2.2	
3/4	20	120.0	105.0	130.0	2.6	
1	25	130.0	124.0	160.0	4.4	
1 1/4	32	140.0	130.0	160.0	5.8	
1 1/2	40	165.0	115.0	230.0	7.1	
2	50	180.0	120.0	230.0	9.0	
2 1/2	65	190.0	155.0	400.0	16.0	
3	80	200.0	165.0	400.0	19.0	
4	100	230.0	200.0	460.0	29.0	
5	125	300.0	220.0	460.0	48.0	
6	150	340.0	295.0	1000.0	70.0	
8	200	450.0	355.0	1500.0	105.0	

Material List

NAME OF PART	MATERIAL	SPECIFICATION
BODY	STAINLESS STEEL	SCS14A
BODYCAP	STAINLESS STEEL	SCS14A
STEM	STAINLESS STEEL	SUS316
BALL	STAINLESS STEEL	SUS316 OR SCS14A

Specifications

10K CAST STAINLESS STEEL,BALL VALVES,Anti-static Device,Full Bore,Flanged Ends.
End Connection:JIS B2220 10K,Wall Thickness:ASME B16.34 CLASS 150,Sizes: 1/2-8
inch(15-200mm),BODY MATERIAL:STAINLESS STEEL,BODYCAP
MATERIAL:STAINLESS STEEL,STEM MATERIAL:STAINLESS STEEL,BALL
MATERIAL:STAINLESS STEEL,KITZ Fig:10UTBM

